

UNITED STATES PATENT APPLICATION

OF

GUNTER GALLAS

AND

HOWARD LEOPOLD

FOR

GROUND FAULT CIRCUIT INTERRUPTER

WITH FUNCTIONALITY FOR RESET

**GROUND FAULT CIRCUIT INTERRUPTER
WITH FUNCTIONALITY FOR RESET**

RELATED APPLICATIONS

[0001] This application is related to provisional and non-provisional utility patent applications which are commonly owned by the assignee of this application and which are incorporated by reference. The related non-provisional utility applications are: Application No. 09/251,426, Attorney Docket No. 034806-5008, by inventors Yuliy Rushansky and Howard S. Leopold, entitled "STANDOFF ASSEMBLY AND METHOD FOR SUPPORTING AN ELECTRICAL COMPONENT", filed February 17, 1999; and Application No. 09/251,427, Attorney Docket No. 034806-5009, by inventors Howard S. Leopold and Yuliy Rushansky, entitled "ELECTRICAL CIRCUIT INTERRUPTER", filed February 17, 1999. In addition, this application is related to provisional patent applications which are commonly owned by the assignee of this application and which are hereby incorporated by reference. The related provisional applications are Application No. 60/167,215 filed on November 24, 1999 by inventor Howard Leopold for "GROUND FAULT CIRCUIT INTERRUPTER WITH FAIL SAFE MODE," and Application No. 60/210,015 filed on June 8, 2000 by inventors Gunter Gallas and Howard Leopold for "GROUND FAULT CIRCUIT INTERRUPTER WITH FUNCTIONALITY FOR RESET."

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The invention relates to an error detection circuit interrupter device that includes a detection circuit for determining whether an error has occurred in an exterior circuit and includes an interrupter device for stopping current flow to the exterior circuit when an error has been detected. More particularly, the invention relates to a GFCI that has a reset device which utilizes a test current to actuate a bistable latching relay and reset the tripped GFCI - thus testing the functionality of the GFCI and resetting the GFCI simultaneously. Furthermore, the invention relates to a ground fault circuit interrupter device (GFCI) with a fail safe mode, wherein the

GFCI is incapable of being reset after a trip if any of its key electrical components malfunction or are not working.

Description of the Related Art

[0003] Fault or error detection devices are well known in the art to provide additional safety for electrical components. A specific type of fault or error detection device is known as a GFCI device. In operation, a GFCI type device supplies electricity to an exterior circuit and opens an outlet circuit when a ground fault occurs in the exterior circuit, i.e., when a portion of a circuit that is plugged into the outlet becomes grounded. For example, if a hair dryer is negligently dropped into a bathtub, electricity may flow from the hair dryer circuit to ground through the bathtub water. A person might be part of the current path to ground. An electrical outlet provided with a GFCI device would detect such a ground fault and, almost instantaneously, open the outlet circuit to prevent current from flowing from the hair dryer circuit to ground. Although the GFCI device is described above as being associated with an outlet, the typical GFCI device can be associated with other different types of electrical junctures.

[0004] Conventional GFCI devices include a detection circuit that compares the current leaving the outlet circuit to the current returning to the outlet circuit. When there is a pre-set differential between the leaving and returning outlet currents, the GFCI opens the outlet circuit and indicates that a ground fault has occurred. The detection circuit can be constructed in a number of different ways, including providing a differential transformer for sensing the imbalance in the current flow. In addition, there are many different structures that have conventionally been used to open the circuit once the ground fault has been detected. For example, some conventional GFCI devices use a trip coil to open the outlet circuit. A test and reset button are also typically provided on the GFCI device for testing whether the device is functioning properly and for resetting the device after testing or after the device has been tripped. Conventional GFCI devices are often complicated structures that require sophisticated manufacturing processes to ensure that they work properly and safely. Conventional GFCI devices, as well as the GFCI device in U.S.

Application No. 09/251,427, do not have a structure for ensuring that the GFCI device cannot be reset when one or more key electrical components, such as the transformer, integrated circuit (IC), solenoid, and solenoid controlling devices are not operable. For example, for the GFCI device of Application No. 09/251,427, if the GFCI unit trips because of a ground fault, the unit can be manually reset by depressing the reset button. If one of the key electrical components is damaged due to the ground fault or by any other means, the GFCI can still be reset so that electricity would be provided to the electrical outlet. In this case however, the GFCI will no longer be able to detect another ground fault and thus will no longer be able to stop current flow to the exterior circuit. Several other drawbacks also exist in other conventional GFCI devices, including high manufacturing cost, poor reliability, poor endurance, potential safety concerns due to excessive heat generation and/or poor reliability, and general aesthetic and ergonomic drawbacks.

SUMMARY OF THE INVENTION

[0005] An object of the invention is to provide a fault/error detection device that is economic to manufacture, requires as few parts as possible and operates at a high level of reliability. Another object of the present invention is to provide a GFCI device that is capable of being reset after a trip only if the GFCI circuit is operational. Another object of the invention is to provide a GFCI device that is incapable of being reset if any of the key electrical components become inoperable. Another object of the invention is to provide a GFCI device that is simple to manufacture and includes as few parts as possible while also providing the structural stability necessary for the device to be tested on a regular basis. Another object of the invention is to provide a GFCI device that includes a test light indicator that will indicate when the GFCI device has been tripped, whether the GFCI device is wired correctly.

[0006] To achieve these and other advantages and in accordance with the purpose of the invention, as embodied and broadly described, the GFCI device includes a switch connected to a current sensing device. The current sensing device is capable of determining whether the outflow of current is different from inflow, and upon sensing a difference between outflow current and inflow current (sensing a possible ground fault), outputting an electrical signal to a

bistable latching relay trip mechanism which then opens the main switch and prevents current from flowing through the GFCI. The device includes a reset switch that sets up a test condition for the GFCI device. If the reset switch is activated and test conditions indicate that the GFCI is functioning properly, an electrical signal is provided to the bistable latching relay switch which then closes the main switch and permits current to pass through the GFCI.

[0007] In accordance with another aspect of the invention, a GFCI device with a fail safe mode prevents restoration of current flow through a first circuit when a component of the GFCI device is malfunctioning or otherwise inoperable. The ground fault circuit interrupter device can include a housing, a substructure located in the housing, a ground fault detector located on the substructure and capable of detecting whether a ground fault has occurred in the first circuit, a current path structure located on the substructure and having a first end terminating at an input connector and a second end terminating at an output connector. The current path structure preferably includes a single electrical splice. A pair of contact points can be located in the current path structure and displaceable from each other to open the current path structure and cause current to stop flowing in the first circuit when the ground fault detector detects that a ground fault has occurred. The means for displacing the contact points can include a latch biased towards a predetermined position by a hairspring at one end and an armature within a solenoid at another end, where displacement of the armature in a predetermined direction causes displacement of the latch to ultimately allow displacement of the contact points.

[0008] In accordance with another aspect of the invention, the GFCI device can include a thermally activated part that, upon being heated by an overheated solenoid coil, moves into a position to block the ability for the GFCI device to be reset. The GFCI reset ability can be blocked by preventing normal movement of the latch or preventing normal movement of the armature. The overheated solenoid is an indication that the GFCI device is malfunctioning and therefore should not be permitted to be reset. The thermally activated part can be, for example, a thermocouple connected to an electrical switching device that moves a locking mechanism into contact with either the latch or the armature when a predetermined "solenoid overheating" temperature is sensed by the thermocouple.

[0009] It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of the specification, illustrate one embodiment of the invention and together with the written description serves to explain the principles of the invention. In the drawings:

[0011] FIGs. 1A and 1B are first and second perspective views of a GFCI device embodying the principles of the invention;

[0012] FIG. 2 is an exploded view of the GFCI device of FIGs. 1A and 1B;

[0013] FIG. 3 A and 3B are exploded and unexploded perspective views, respectively, of the PC board assembly as shown in FIG. 2;

[0014] FIG. 4 is an isometric view of the back of the top housing cover as shown in FIG. 1A;

[0015] FIG. 5 is an isometric view of the back of the bottom housing cover as shown in FIG. 1B;

[0016] FIGs. 6A and 6B are isometric views of the hot current path and neutral current path, respectively, of the GFCI device as shown in FIG. 2;

[0017] FIGs. 7A-7D are top, first isometric, bottom, and second isometric views of the middle housing as shown in FIG. 2;

[0018] FIGs. 8A-8D are first and second isometric views of the hot output terminal and first and second isometric views of the neutral output terminal, respectively, of the GFCI device of FIG.2;

[0019] FIGs. 9A and 9B are isometric views of the hot contact arm and the neutral contact arm, respectively, of the GFCI device as shown in FIG. 2;

[0020] FIG. 10A-10D are first and second perspective views of the neutral input terminal and first and second perspective views of the hot input terminal, respectively, of the GFCI device as shown in FIG. 2;

[0021] FIG. 11 is an isometric view of the test button of the GFCI device as shown in FIG. 2;

[0022] FIGs. 12A and 12B are first and second isometric views, respectively, of the latch block assembly as shown in FIG. 2;

[0023] FIG. 13 is an exploded view of the latch block assembly shown in FIG. 12;

[0024] FIGs. 14A and 14B are first and second isometric views, respectively, of the solenoid and solenoid bobbin as shown in FIG. 2;

[0025] FIGs. 15A and 15B are first and second isometric views, respectively, of the solenoid clip as shown in FIG. 2;

[0026] FIGs. 16A and 16B are first and second isometric views, respectively, of the transformer boat as shown in FIG. 2.

[0027] FIG. 17 is a perspective drawing of the circuit desensitizing switch for the GFCI device as shown in FIGs. 2;

[0028] FIGs. 18A-18D are sequential skeleton drawings of the trip/reset structure for the GFCI device as shown in FIG. 2;

[0029] FIGs. 19A-19C are schematic views of the GFCI device in a "reset", "trip due to a ground fault" and "electronic component malfunction" state, respectively; and

[0030] Fig. 20 is a flow chart of an embodiment of the invention including a bistable latching relay to test the functionality of the GFCI during reset operations.

[0031] Fig. 21 is a block diagram of another embodiment of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0032] Reference will now be made in detail to the present preferred embodiment of the invention, an example of which is illustrated in the accompanying drawings.

[0033] FIG. 1A shows a GFCI device 1 that is constructed in accordance with the principles of the invention. The GFCI device can have a top housing cover 100 that is constructed of a size and shape that is consistent with industry standards for an electrical outlet. Preferably, the device includes two sets of receptacle openings for receiving standard plugs. A test/reset aperture can be located along a mid-line of the top housing cover 100 and include a test button 801 and reset button 802 located therein. A light aperture 108 can also be located on the mid-

line of the top housing cover **100** to enclose a light for indicating whether the GFCI device has been tripped due to either a ground fault detection or a test of the device. The light can also indicate whether the GFCI device has been correctly wired and whether the key electrical components are functioning properly.

[0034] Top and bottom angled indicia surfaces **101** can be provided on either side of the mid-line and include indicia thereon. The indicia can include numerals, letters, symbols or other markings that can be viewed from the exterior of the GFCI device and which preferably provide an instructional message to a viewer. In the embodiment depicted in FIG. 1A, the indicia comprise the terms “test” and “reset” to instruct a viewer of the function of the buttons located adjacent the indicia surfaces. The angled indicia surfaces are preferably sloped at a 45° angle with respect to the substantially planar face surface **107** of the top housing cover **100** so that the indicia can be read from above and below the GFCI device. Accordingly, a user can read the indicia on the angled indicia surfaces **101** regardless of the orientation of the GFCI device when installed. Furthermore, it should be appreciated that this preferred configuration de-emphasizes the visual appearance of indicia on the top indicia surface and emphasizes indicia located on the bottom indicia surface when viewed from above, e.g., when the device is installed in a wall.

[0035] A mounting strap **920** extends from either side of the top housing cover **100** for attaching the GFCI device to a wall box. Indents **103** can be provided on either side of the top housing cover **100** to facilitate connection to electrical wires.

[0036] FIG. 1B shows an isometric view of the bottom housing cover **200** which is attached to the top housing cover **100** via screws inserted through the connection holes **201** in the bottom housing **200**. Neutral connection holes **202** and hot connection holes **203** are located in the bottom housing cover **200** to provide an alternate connection for input wires onto the GFCI circuit. In addition, neutral connection holes **204** and hot connection holes **205** are located on the bottom housing cover **200** to provide an alternate attachment structure for output wires leading from the GFCI circuit. A wide pathway **206** can be located at one end of the periphery of the bottom housing cover **200** to facilitate attachment of a U-shaped wire connector to the grounding screw of the GFCI device. Indents **208** may also be provided on the bottom housing cover **200**

and aligned with the indents **103** of the top housing cover **100** to provide clearance for U-shaped wire attachment structures for input and output wires.

[0037] As shown in FIG. 2, the top housing cover **100** and the bottom housing cover **200** encase the GFCI components and circuitry including a middle housing **300** and circuit board **950** therebetween. The middle housing **300** is located above the circuit board **950** and adjacent the top housing cover **100**. The circuit board **950** rests adjacent the bottom wall of the bottom housing cover **200**. The middle housing **300** can be a one piece molded structure that has a plurality of ribs thereon to locate and stabilize the GFCI circuit components. A mounting strap **920** can be sandwiched between the top housing cover **100** and the middle housing **300** and extend from either end of the GFCI device so that the GFCI device can be mounted to a conventional wall box.

[0038] The GFCI circuitry as shown in FIG. 2 includes a transformer device for detecting a ground fault, a solenoid trip device for causing both current pathways of the GFCI device to open, and a test/reset structure for periodically testing the GFCI device and for resetting the GFCI device after it has been either tested or tripped.

[0039] FIGs. 3A and 3B depict an exploded view and an isometric view, respectively, of the electronic components **951** and other various components that are located on the circuit board **950** of the GFCI device. The electronic components **951** include resistors, capacitors and other well known electronic circuit components for comprising a GFCI circuit. The electronic components **951** can be attached to the circuit board **950** via any well known attachment method, e.g., by soldering. The circuit board **950** can include clip apertures **952** and pivot apertures **953** for attaching the transformer boat **400** and the solenoid bobbin **700** quickly and easily with lock/alignment pins and clips located on the base of each of the transformer boat **400** and solenoid bobbin **700**.

[0040] The test light **901** can be raised from the circuit board **950** by the standoff **900**. The standoff **900** is preferably a two-piece snap together structure as described in applicant's co-pending patent application filed on same date and incorporated herein by reference.

[0041] Elements of the current path can be attached to the circuit board at a hot attachment point and a neutral attachment point. Specifically, hot contact arm **520** and hot input terminal **550** can be soldered together and to the circuit board **950** at a location underneath the transformer boat **400**. Likewise, the neutral contact arm **620** and neutral input terminal **650** can be soldered together and to the circuit board **950** at a location underneath the transformer boat **400** and adjacent to the hot attachment point. Accordingly, electrical power can be supplied to the electronic components **951** and all other electronic devices located on the circuit board **950** via the hot input terminal **550** and neutral input terminal **650**.

[0042] As shown in FIG. 4, the top housing cover **100** can include tapped or self tapping attachment holes **102** located at the corners of the top housing cover **100** for screw connection to the bottom housing **200**. Contact cavities **104** are shown located in the central portion of the top housing cover **100** for sealing and protecting the area in which contacts are located in the hot and neutral current paths. Test reset aperture **105** can be configured as a long, narrow rectangular opening in the central portion of the top housing cover **100**. The test/reset aperture **105** permits the test button **801** and reset button **802** to be contactable from outside of the top housing cover **100**.

[0043] A reset pin guide **106** can be formed as part of the back surface of the top housing cover **100** to stabilize and guide the motion of the reset button **802** and shaft **804** in a linear path when they are actuated.

[0044] Light aperture **108** can be located adjacent the test/reset aperture **105** for convenient viewing. The test light **901** is aided by the standoff **900** to extend from the circuit board **950** and into the light aperture **108**.

[0045] Ground hole **110** and slots **109** are shown arranged in the North American standard configuration for household electrical outlets. Although not shown, other configurations for the ground hole **110** and slots **109** are well known for complying with other types of electrical plugs as appropriate in various area of the world and for various applications.

[0046] As shown in FIG. 5, the bottom housing **200** can be a unitary one piece structure that is generally rectangular in shape and includes connection holes **201** located at each corner. The

connection holes **201** are in alignment with the attachment holes **102** in the top housing cover **100** for connecting the top and bottom housing covers **100, 200** by a screw, nail or other fastening device.

[0047] The bottom housing **200** of the GFCI device can be configured with several different input and output connection options. In particular, indents **208** can be provided at the sides of the bottom housing **200** to facilitate connection between a U-shaped connector on an input wire to a screw/face terminal connection **961** provided on one of the current pathways of the GFCI circuitry. In addition, bottom housing **200** can be provided with neutral input connection holes **202**, hot input connection holes **203**, neutral output connection holes **204** and hot output connection holes **205**. The connection holes **202-205** permit bare electrical lines access to the GFCI circuitry. Specifically, a bare wire inserted into one of the connection holes **202-205** can be guided to an area between a connection face plate **963** and its associated wire connector surface, e.g., wire connector **508, 551, 608** or **651**. After insertion, the bare wire can be clamped into connection with one of the current pathways by turning a screw of a screw/face terminal to cause the connection face plate **936** to close onto and clamp the bare wire between the connection face plate **963** and a wire connector **508, 551, 608** or **651**. The connection face plate **963** can include horizontal grooves therein to prevent a bare wire connected thereto from slipping out of connection with the connection face plate **963**. A bare wire connection can be made alternatively or in addition to the connection of a U-shaped wire terminal to the screw/face terminals **961** located at the sides of GFCI housing.

[0048] The screw/face terminals **961** can be situated in the bottom housing **200** such that they can be connected to either a U-shaped connector on the end of a wire at indent **208** or to a bare wire that is inserted into one of the connection holes **202-205**. The U-shaped wire terminal can be clamped between the screw head of the screw/face terminal **961** and the outer surface of one of the wire connectors **508, 551, 608** or **651**.

[0049] Figs. 6A and 6B show the hot and neutral current pathway structures, respectively, of the GFCI device. FIG 6A depicts the various structures that make up the hot current pathway for the GFCI device and shows their relative position as assembled. The hot current pathway can

consist of a hot input terminal **550**, hot contact arm **520** two contacts **501** and **521** and a hot output terminal **500**. The hot input terminal **550** can be configured to be attachable to an electrical wire for receiving positive (hot) current into the current pathway. The hot input terminal **550** can be attached to the hot contact arm **520** by soldering or the like. Additionally, both the hot input terminal **550** and hot contact arm **520** can be anchored to the circuit board **950** by the same solder connection that connects the two structures together. The hot contact arm **520** can be figured to include a contact stem **522** that extends through the center of a transformer coil **408** located in the transformer boat **400** when assembled. Current passing through the contact stem **522** is compared by the transformer coil **408** to the current returning through a similar contact stem **622** located on the neutral contact arm **620**. In accordance with the laws of physics, an electrical current will be induced in the transformer coil **408** when there is a differential between the current flows in contact stems **522** and **622**. Once a predetermined current is induced in the transformer coil **408**, a ground fault will be indicated by the GFCI device and the current paths will be opened as explained later.

[0050] The hot contact arm **520** can be separably connected to the hot output terminal **500** via a pair of contacts **501**, **521**. Contact **521** can be located on a cantilevered arm portion the hot contact arm **520** and contact **501** can be located on a stationary arm of the hot output terminal **500**. Accordingly, a downward force applied to the cantilevered arm portion will force the contact **521** out of contact with the contact **501** located on the hot output terminal **500** to open the hot current pathway. The hot output terminal **500** can be separably connected to the hot contact arm **520** as explained above and can include two conventional spring type electrical receptacle contacts **504** and a wire connector **508**. The wire connector **508** and receptacle contacts **504** can be connected to an outside circuit, e.g., to an appliance, other electrical device or other electrical receptacle.

[0051] As shown in FIG 6B, the neutral current pathway structure can consist of a neutral input terminal **650**, a neutral contact arm **620**, a pair of contacts **601**, **621** and a neutral output terminal **600**. The neutral input terminal **650** can be attached to an electrical wire at one end and soldered to the circuit board **950** and the neutral contact arm **620** at the opposite end. The neutral contact

arm **620** includes a contact stem **622** that can be positioned adjacent the contact stem **522** of the hot contact arm **550** and through the transformer coil **408** to allow ground fault detection as explained above. Contact **621** can be located at a distal end of a cantilevered arm portion of the contact arm **620** and contact **601** can be located on a stationary arm of the neutral output terminal. The cantilevered arm portion is configured such that contact **621** will separate from contact **601** when a downward force is applied to the cantilevered arm portion of the contact arm **620**. Accordingly, the neutral current pathway can be opened by a linear downward force applied to the cantilevered arm portion. In addition, the hot contact arm **520** and neutral contact arm **620** can be located adjacent each other when assembled into the GFCI housing such that a single structure, e.g., latch block assembly **810**, can provide the downward linear force necessary to simultaneously open both the hot and neutral current pathways. The neutral output terminal **600** can be separably connected to the neutral contact arm **620** at contact point **601** as explained above. The neutral output terminal **600** also includes two conventional spring type electrical receptacle contacts **604** and a wire connector **608** for connecting a neutral electrical conductor between the GFCI device and an appliance or other electrical device or receptacle.

[0052] As shown in FIGs. 7A-7D the middle housing **300** can be molded from a unitary piece of plastic and be configured to fit within and be clamped between the top housing cover **100** and bottom housing cover **200**. The middle housing **300** is preferably a different color as compared with the top housing **100** and bottom housing **200** to more clearly indicate where electrical wires can be connected to the GFCI device. For example, the middle housing **300** is preferably blue while the top housing **100** and bottom housing **200** are preferably white and grey, respectively. A pair of contact arm through holes **306** can be provided in the central area of the middle housing **300** so that the far end of the cantilevered portions of the hot and neutral contact arms **520** and **620**, can pass through the middle housing **300** allowing each pair of contacts **501**, **521** and **601**, **621** to contact each other. Thus, the middle housing **300** protects the circuit board **950** from any sparking that may occur between pairs of contacts **501**, **521** and **601**, **621** when they are separated from or contacted to each other.

[0053] The top portion of the middle housing 300 can be configured to align the hot output terminal 500 and the neutral output terminal 600 and to electrically separate both of these structures from each other and from the components located on the circuit board. The hot output terminal 500 and neutral output terminal 600 can be located between the top housing cover 100 and the middle housing 300 such that a conventional plug will have access to the hot output terminal 500 and neutral output terminal 600 when inserted through slots 109 in the top housing cover 100.

[0054] A test resistor through hole 304 in the central portion of the middle housing allows a test resistor to pass therethrough. As will be explained in more detail later, the test resistor allows the GFCI device to be tested by simulating a ground fault by diverting current through the test resistor from the hot output terminal and eventually to the neutral input terminal through the circuit board 950. A light standoff through hole 302 can be located in the middle housing 300 to support the standoff 900 as it extends from the circuit board to the top housing cover 100.

Likewise, a reset shaft through hole 320 can be placed in a central area of the middle housing 300 to permit the reset shaft 804 to pass therethrough and to guide the reset shaft 804 along a linear path. In addition, the reset shaft through hole 320 includes a countersunk portion on the bottom side of the middle housing, as shown in FIG. 7C and 7D, that allows a latch block 820 and latch block actuation spring 812 to reside therein. Accordingly, the reset shaft through hole structure guides the latch block 820 along the same linear path as taken by the reset shaft when moved.

[0055] A hot output terminal throughway 316 and a neutral output terminal throughway 318 can be located at either side of the middle housing to allow the U-shaped wire connectors 508 and 608 to pass through the middle housing 300 and be exposed at either side of the GFCI device for connection to electrical wires. A test button guide way 322 can be located in the top portion of the middle housing 300 for guiding the test button 801 along a linear path and into contact with the test switch arm 502 of the hot output terminal 500. The test button 801 can be located above and guided within the top portion of the middle housing 300 above the test resistor through hole 304.

[0056] The bottom portion of the middle housing 300 can include alignment holes 324 that mate with alignment posts 419 located on the transformer boat 400. Alignment between all of the components of the GFCI device is important to ensure that the hot and neutral contacts 501, 521 and 601, 621, respectively, remain in contact with each other when the GFCI device is in its "reset position" and to ensure that the contacts will be out of contact with each other when the GFCI device is in its "tripped position." A transformer boat indent 308 and a solenoid bobbin indent 314 can be provided in the bottom portion of the middle housing 300 to secure and align the transformer boat 400 and solenoid bobbin 700. A hot contact arm indent 310 and a neutral contact arm indent 312 can be separated from each other by a separation wall 326 to provide alignment structures for the hot and neutral contact arms 520 and 620, respectively, to reside in. The separation wall 326 also electrically insulates the contact arms 520 and 620 from each other.

[0057] Screw/face supports 327 can extend from the bottom of the middle housing 300 and into the central opening of the U-shaped wire connectors 551 and 651 located on the hot input terminal 550 and neutral input terminal 650, respectively. The screw/face supports 327 serve to retain the screw/face terminals 961 in a general area and provide support when the screw/face terminals 961 are used to lock down an electrical wire.

[0058] As shown in FIGs. 8A-8D, the hot output terminal 500 and neutral output terminal 600 can each be constructed as a one-piece structure that is made from an electrically conductive material such as brass. The hot output terminal 500 can include two receptacle contacts 504 that are disposed adjacent slots 109 in the top cover housing 100 when assembled. As shown in FIG. 8A, the receptacle contacts 504 are standard spring receptacle contacts that are adapted to receive a standard 120V North American plug. However, different receptacle contacts can be used depending on the location and application of the GFCI device. U-shaped wire connector 508 extends from one end of the hot output terminal such that, when assembled, it will be located at and accessible from the side of the GFCI device for attachment to an electrical wire. A contact 501 configured for connection to a contact 521 on the hot contact arm 520 can be located on an arm that extends laterally from the hot output terminal 500. The extended arm portion of the hot output terminal 500 is relatively short and rigid such that the attached contact 501 remains

stationary with respect to the hot output terminal **500** and the middle housing **300** in which the hot output terminal **500** resides.

[0059] A test switch arm **502** can be provided as an integral lateral extension from the hot output terminal **500**. The test switch arm **502** can be configured to reside over the test resistor through hole **304** and under the test button **801** when assembled in the GFCI device. The test switch arm **502** is also of such a length and rigidity that depression of the test button **801** from outside the GFCI device will cause the test button **801** to contact and bend the test switch arm **502** into contact with a test resistor located in the test resistor through hole **304** of the middle housing **300**. Current that flows from the hot output terminal **500** through the test switch arm **502** to the test resistor will (if the GFCI device is operating correctly) cause the GFCI device to indicate a ground fault has occurred and subsequently trip the GFCI device to open the current pathways.

[0060] The neutral output terminal **600** can also include two receptacle contacts **604** constructed in a similar fashion as are receptacle contacts **504** of the hot output terminal **500**. A wire connector **608** can also be provided on the neutral output terminal **600**. A contact **601** can be provided on a relatively short and rigid extension arm on the neutral output terminal **600** for connection to a contact **621** located on the neutral contact arm **620**.

[0061] As shown in FIGs. 9A and 9B, hot contact arm **520** and neutral contact arm **620** can each be configured as a unitary structure that is basically a mirror image of each other. The hot contact arm **520** can include a contact stem **522** that is designed to extend through the center of transformer coils **408** in the transformer boat **400**. A distal end of the contact stem **522** can be soldered, welded or otherwise electrically connected to both the circuit board **950** and connecting tab **552** of the hot input terminal **550**. The opposite end of the contact stem **522** includes a stop tab **526** that extends from a side of the contact stem **522** for abutting against the transformer boat **400**. The stop tab **526** ensures the correct insertion depth of the contact stem **522** into the circuit board and correctly aligns the hot contact arm **520** with the transformer boat **400** and GFCI circuitry. The hot contact arm **520** includes a series of bends at its middle portion to navigate around the transformer boat structure. Another stop tab **526** and an alignment post **524** can extend into transformer boat **400** and are located in the middle portion of the contact arm **520** to

align the contact arm **520** within the GFCI device. A cantilevered arm portion extends from the middle portion and has a through hole at its distal end for connection to contact **521**. When assembled in the GFCI device, the cantilevered arm portion extends through the middle housing such that contact **521** is normally in contact with contact **501** of the hot output terminal **500**. In addition, the cantilevered arm portion is of such a length and dimension that it can be forcibly flexed about a position adjacent to the alignment post **524**. Accordingly, contact **521** can be in contact with contact **501** when in the reset position and forcibly flexed away from and out of contact with contact **501** when in the tripped position. The stop tabs **526** and alignment tab **524** ensure that the contact arm **520** is positioned correctly so that the contacts **501** and **521** will be in contact and out of contact in their reset and tripped positions, respectively. In particular, alignment tab **524** is designed to extend into an alignment tab receptacle **422** in the transformer boat **400** at a depth set by stop tab **526** to secure the position of the contact arm **520** with respect to the transformer boat **400**. In addition, the alignment tab **524** and stop tab **526** create an anchor point from which the cantilevered arm portion can flex.

[0062] The neutral contact arm **620** can include similar structures that perform relatively identical functions as compared to the hot contact arm **520**. Moreover, neutral contact arm **620** can include stop tabs **626** and alignment tab **624** for alignment with the transformer boat **400** and for providing an anchor point for a cantilevered arm portion of the neutral contact arm **620**. Contact stem **622** is designed to extend through the transformer boat **400** adjacent to the contact stem **522** of the hot contact arm **520** and be similarly electrically attached to both the circuit board **950** and the corresponding neutral input terminal **650** at a distal end of the contact stem **622**. A contact **621** can be located at a distal end of the cantilevered portion of the neutral contact arm for connection to contact **601** of the neutral output terminal when in the reset position, and for forcible separation from the contact **601** when in the tripped position.

[0063] As shown in FIGs. 10A-10D, the neutral input terminal **650** and hot input terminal **550** can each be a one-piece unitary structure made from electrically conductive material. The neutral input terminal **650** can be an approximate mirror image of the hot input terminal **550** and include a U-shaped wire connector **651**, a connection tab **652** and a pair of mounting tabs **654**.

The mounting tabs **654** and connection tab **652** can be assembled onto the circuit board **950** such that they extend through and are soldered onto the circuit board **950**. Connection tab **652** can also be soldered to the contact stem **622** of the neutral contact arm **620** such that electrical current can pass between the neutral contact arm **620** and neutral input terminal **650**. The U-shaped wire connector **651** can be arranged at an approximate 90 degree angle with respect to the base of the neutral input terminal **650** so that, when installed, the wire connector **651** is located at and accessible from a side of the GFCI device. The location of the wire connector **651** provides easy connection to an electrical wire via the screw/face terminal **961**.

[0064] As stated above, the hot input terminal **550** can be constructed as an almost identical mirror image of the neutral input terminal **650**. Specifically, the hot input terminal **550** can include a U-shaped wire connector **551** that is configured at a 90 degree angle with respect to a base portion of the hot input terminal **550**. Mounting tabs **554** and connecting tab **552** can extend from the bottom of the base portion for electrical connection to the circuit board **950** via soldering or other known permanent electrical connection. The connection tab **552** can also be electrically connected to the contact stem **522** of the hot contact arm to create a current pathway therebetween.

[0065] As shown in FIG. 11, test button **801** can be formed of a single-piece non-conductive material, for example, plastic. The test button **801** is design to have a push surface (as shown in FIG. 1A) that extends from the test/reset aperture **105** in the top housing cover **100**. The test button **801** can be depressed by a user to cause the GFCI circuitry to simulate a ground fault detection, thereby testing whether the GFCI device is working properly. Stop flanges **808** can be located at either side of the test button **801** to abut a side of the test/reset aperture **105** and prevent the test button **801** from being removed from the top housing cover **100**. A test switch arm contact surface **803** can be located below the push surface of the test button **801** and at the end of an extension supported by guide rib **809**. The contact surface **803** can be designed to contact the test switch arm **502** of the hot contact arm such that the resiliency of the test switch arm **502** keeps the test button in a protruded state from the test/reset aperture **105** in the top housing cover **100**. In addition, when the test button **801** is depressed, the contact surface **803**

can be situated such that it forces the test switch arm **502** to flex downward and contact a test resistor located in the test resistor throughway **304** to simulate a ground fault and test whether the GFCI device is operating properly. The test button **801** can be guided along a linear path during depression by guide rib **809** acting in conjunction with the test button guide way **322** in the middle housing **300**.

[0066] As shown in FIGs. 12A, 12B and 13, latch block assembly **810** can include two major components: a latch block **820** and a latch **840**. The latch block assembly **810** works in conjunction with other elements of the GFCI device to perform various functions, including retaining the reset shaft **804** in its “reset” position, or, causing the contacts **501**, **521** and contacts **601**, **621** to decouple from each other to open the GFCI circuitry when a ground fault is detected or if a key electronic component malfunctions. The latch block **820** can be T-shaped with arms **821** that extend from opposite sides of a main body portion **826** and a shield tube **822** that extends from the main body portion and is located between the arms **821**. A through hole **824** extends through the shield tube **822** to the opposite side of the main body portion **826**. Latch guides **823** can be formed at the bottom of the latch block **820** and on either side of the through hole **824** for guiding the latch **840** along the bottom surface of the latch block **820**. When assembled, an hour-glass shaped opening in the latch **840** corresponds with the through hole **824** of the latch block **820** to permit the reset shaft **804** to pass through. The shield tube **822** provides protection from the possibility of any arcing to the reset shaft **804** and/or other structures during operation.

[0067] Latch **840** can be slidably located in the latch guides **823** and includes a latch middle portion **843** for locking into latch groove **805** of the reset shaft **804** when in the reset position. As shown in FIG. 12B, the latch **840** also includes two cutouts **845** and **846** adjacent to the middle portion. Cutout **845** allows reset shaft **804** to be activated in the event of a ground fault. Cutout **846** allows reset shaft to be activated if any of the key electrical components of the GFCI malfunction. As shown in FIG. 19A, the latch middle portion **843** is maintained in the latch groove **805** of the reset shaft **804** by means of the solenoid armature **712**. The solenoid armature **712**, which contacts the strike plate **841** of the latch **840** at end **713**, maintains latch middle

portion **843** at a predetermined position in latch groove **805** of reset shaft **804**, against the bias of hairspring **844**, which is maintained in hole **847** of latch **840**. The latch **840** can include a pair of catch tabs **842** located on either side of an end of the latch **840** opposite the striking plate **841**. Catch tabs **842** are bent slightly downward such that they can pass through latch guides **823** during assembly and then spring outward after assembly to prevent removal of the latch **840** as a result of contact between catch tabs **842** and either the latch block **820** or the latch guides **823**.

[0068] As will be discussed in detail later, the latch block assembly **810** is slidably mounted on the reset shaft **804** such that a latch block actuation spring **812** (shown in FIG. 18) can cause the latch block assembly to slide down the reset shaft to disengage contacts **501**, **521** and **601**, **621** and thus open the GFCI circuitry current pathways when a ground fault is detected.

[0069] As shown in FIGs. 14A-14B, solenoid bobbin **700** can include a solenoid frame **733**, solenoid winding **703** and solenoid armature **712** (as shown in FIG. 2). Solenoid winding **703** can be wound on a spool **731** located between solenoid end plates **704** and **705**. The solenoid functions to trip the latch **840** of the latch block assembly **810** when a ground fault is detected, such that latch groove **805** of the reset shaft **804** is released from the middle portion **843** of latch **840**, by means of the solenoid armature **712**. Once the latch **840** releases the reset shaft **804**, the latch block actuation spring **812** forces the latch block assembly **810** to slide along the reset shaft **804** and eventually contact the cantilevered portion of the hot and neutral contact arms **520** and **620**. Accordingly, contacts **501**, **521** and **601**, **621** are caused to separate from each other, and the current pathways are thus opened by the downward sliding motion of the latch block assembly **810** when a ground fault is detected.

[0070] The solenoid bobbin **700** can include a one-piece solenoid frame **733** that is preferably made from a plastic material. A spool **731** with end-plates **704** and **705** bordering the spool **731** can be located at one end of the frame **733**. A rectangular window portion **732** can be located at the opposite end of the solenoid frame **733**. The rectangular window **732** can include a reset shaft throughway **710** for guiding the reset shaft **804** when it is depressed to reset the latch block assembly **810** to its reset position. A component support **708** preferably extends from a side of the rectangular window portion **732** for providing support for and protecting an electrical

component **951** extending from the circuit board **950**. A shelf **706** can be located at a distal end of the rectangular window portion **732**. Shelf **706** is designed to mate with a support arm **404** located on the transformer boat **400** and cooperate therewith to provide added support to the circuit board **950** and transformer boat **400**. Specifically, shelf **706** resides under and is in overlapping contact with the support arm **404** such that when the circuit board **950** is flexed or bent at a location between the transformer boat **400** and solenoid bobbin **700**, the shelf **706** and support arm **400** prevent substantial movement of the circuit board **950** in the flexing or bending directions. In addition, contact between support arm **404** and shelf **706** provides reliable support to test resistor throughway **402** to ensure correct positioning of the throughway **402** and test resistor.

[0071] The solenoid bobbin **700** can be attached to the circuit board by a pivot and clip mechanism in which an alignment extrusion **720** that extends from the base of the shelf **706** is placed within a pivot aperture **953** in the circuit board **950**. The solenoid bobbin **700** can then be pivoted downward about the alignment extrusion **720** to lock a snap-in lock hook **718** into a clip aperture **952** in the circuit board **950**. The snap-in lock hook **718** can be located on the end of the rectangular window portion **732** opposite the alignment extrusion **720**. In addition, the snap-in lock hook **718** can be constructed to flex upon entry into the clip aperture **952** and then return to its original configuration once the hook portion of the snap-in lock hook **718** has passed through the clip aperture **952**. Thus, the snap-in lock hook **718** permanently attaches the solenoid bobbin **700** in place on the circuit board **950**.

[0072] The spool portion **731** of the solenoid bobbin **700** includes a wire relief slot **709** for protecting the initial starting portion of wire of the solenoid winding from being damaged by the winding process. An armature throughway **719** can extend through the spool **731** and open into the rectangular window portion **732**. The armature throughway **719** preferably includes guidance/friction reducing ribs **730** that guide and facilitate easy movement of a solenoid armature **712** located within the armature throughway **719**. The armature **712** is preferably a metallic cylinder shaped structure that includes an armature tip **713** at one end. The armature tip

713 can be configured to contact the striking plate 841 of the latch 840 whenever the armature 712 is propelled by the energized solenoid winding 703.

[0073] First and second terminal holes 707 can be located on the bottom corners of end plate 705 for connection to the circuit board 950. The first and second end of the wire that forms the solenoid winding 703 can be attached to first and second terminal pins that extend into terminal holes 707 from the circuit board to supply electrical power from the circuit board 950 to the solenoid. Upon receiving power from the circuit board, the magnetic field created by solenoid winding 703 forces the solenoid armature 712 towards striking plate 841 of the latch 840 to move the latch against the bias of hairspring 844.

[0074] As shown in FIGs. 15A and 15B, a solenoid bracket 702 can be a single-piece structure that includes two arms extending from a base to form a U-shaped bracket. An alignment dimple 721 can be provided on the inside surface of one of said arms to align the bracket within the armature throughway 719 of the solenoid frame 733. A throughway is provided at the center of the dimple to permit the armature tip 713 to pass through when actuated and contact the striking plate 841. An armature throughway 714 can extend through the other of said arms of the solenoid bracket 702 to permit the armature 712 to pass therethrough. The armature throughway 714 can include a key notch 716 that rides over and locks onto a locking ramp 711 in the solenoid end plate 705.

[0075] As showing in FIGs. 16A and 16B, the transformer boat 400 can be a relatively cylindrical object having a plurality of arms 418 extending from the sides of the cylindrical structure. The transformer boat 400 can include a pair of transformer coils 408 that are separated by a first insulating washer 407 and covered by a second identical insulating washer 407. Insulating washers 407 can be provided with indents around its inner diameter that allow the washer to easily flex over and lock onto the inner cylindrical portion 405. A contact stem throughway 406 and throughway separator 416 can be provided through the center of the inner cylindrical portion 405 for allowing contact stems 522 and 622 to pass on either side of throughway separator 416. The throughway separator 416 can include a pair of ridges that run through the center of the contact arm stem throughway 406 and ensure that the hot and neutral

contact stems **522** and **622** do not contact each other, arc between each other, or otherwise short each other out. In a preferred embodiment, the pair of ridges can be formed as a single thick ridge.

[0076] An outer cylindrical portion **409** can encase the transformer coils **408** and include a plurality of arms **418** extending therefrom to stabilize the transformer boat **400** by spreading out the points of attachment with the circuit board **950**. In addition, the plurality of arms **418** create an enclosure around the screw/face terminals **961** to keep the connection face plates **963** from turning and contacting other internal parts of the GFCI device. An alignment post **419** can be integrally formed on the top side of each arm **418** for extension into corresponding alignment holes **324** in the middle housing **300** to ensure alignment of all GFCI components. In addition, contact arm alignment receptacles **422** can extend along a side of the outer cylindrical portion **409** so that alignment tabs **524** and **624** of the hot and neutral contact arms **520** and **620**, respectively, can be inserted therein. The specific configuration of the alignment receptacles **422** ensures the critical alignment of the contact arms **520** and **620** with the hot and neutral output terminals **500** and **600**.

[0077] As discussed previously with respect to the solenoid bobbin **700**, a support arm **404** can extend from the outer cylindrical portion **409** of the transformer boat **400** to contact with the shelf **706** of the solenoid bobbin. The support arm **404** and shelf **706** cooperatively strengthen the flexural stability of the circuit board **950**. In addition, support arm **404** can be provided with a test resistor throughway **402** that is configured to encapsulate and stabilize the top of a resistor while allowing a resistor lead to extend through the throughway **402** and be bent over the structure forming the throughway **402**. The shelf **706** further secures the correct positioning of the test resistor throughway **402** when the test button is depressed. Accordingly, the test resistor lead will be precisely located within the GFCI device and will ensure the working accuracy of the test button. Specifically, test switch arm **502** will be able to repeatedly contact the lead of the test resistor with a high degree of certainty.

[0078] The base of the transformer boat **400** can include a lock/alignment pin **412**, lock clip **414** and a set of terminal pins **420**. The lock alignment/pin extends from the base of the transformer

boat and fits into a pivot aperture **953** in the circuit board **950**. Lock clip **414** also extends from the base of the transformer boat **400** and, during assembly, is flexed into a clip aperture **952** in the circuit board to lock the transformer boat **400** securely to the circuit board **950**. Terminal pins **420** also protrude from an extension of the base of the transformer boat **400** and are electrically connected to the circuit board **950** by soldering or other known attachment structure. Terminal pins **420** are also electrically connected to the transformed coils **408** and communicate to the GFCI circuitry any current changes in the hot and neutral contact arm stems **522** and **622** as sensed by the coils **408**.

[0079] As shown in FIG. 17, circuit desensitizing switch **850** can be configured as a one-piece structure that has two arms **852** and a contact extension **853**. The arm **852** and contact extension **853** extend from a base **854** of the desensitizing switch **850**. A tab **855** can be soldered to the circuit board **950** to keep the contact extension **853** centered over a desensitizing contact **851** located on the circuit board **950**. When assembled, the base **854** can be electrically connected to the circuit board **950** by a tab **855** that extends from a window of the base portion **854**. Two side wings **856** can extend from either side of the base **854** for securing the switch **850** between the solenoid bobbin **700** and the circuit board **950**. The arms **852** and contact **853** can be cantilevered upwards and away from the base portion **854** such that they are resiliently positioned over the circuit board. Specifically, the cantilevered configuration permits contact **853** to be resiliently situated above desensitizing contact **851** (shown in FIG. 18A) located on circuit board **950**. Contact **853** and arms **852** are also located immediately underneath and along a linear path of the latch block assembly **810**. Accordingly, contact **853** can be depressed by the action of side wall ends **857** pressing on arms **852** when latch block assembly **810** moves into its fully tripped position to cause contact **853** to connect with desensitizing contact **851** and deactivate the GFCI device. Thus, the GFCI device can be prevented from sensing further ground faults or activations of the test button until it is reset by the test/reset switch **800**.

[0080] The operation of the test/reset switch **800** will be explained with reference to the sequential skeletal drawings of FIGs. 18A-18D and FIGs. 19A-19C. FIGs. 18A and 18B show the GFCI device in its "tripped" position after the device has sensed a ground fault, the test

button has been depressed and the device has not yet been reset, or an electrical component has malfunctioned.

[0081] In the “reset” position as shown in FIGs. 18C and 18D, the latch block assembly **810** is retained adjacent the middle housing **300** and above and out of contact with the contact arms **520** and **620**. Thus, the hot and neutral current pathways of the GFCI device are closed and permit current to flow to a circuit connected to the GFCI device. Moreover, the elasticity of the cantilevered portions of contact arms **520** and **620** keep the contacts **521** and **621** in electrical connection with contacts **501** and **601** of the hot and neutral output terminal, respectively, to keep the hot and neutral pathways closed when the GFCI device is in its “reset” position.

[0082] The latch block assembly **810** is retained in the “reset” position by latch **840**, where the middle portion **843** of the latch **840** is locked into latch groove **805** of the reset shaft **804**. The locked connection between the latch **840** and the latch groove **805** keeps both the reset spring **811** and the latch block actuation spring **812** in a compressed state. In the “reset” position, the reset button **802** can be slightly spaced apart from the top housing cover **100**. This spacing results from compressive forces of reset spring **811** forcing the shield tube **822** of the latch block **820** into contact with the middle housing **300**. The position at which the reset shaft **804** is locked by latch **840** to the latch block assembly **820** prevents the reset shaft **804** and reset button **802** from extending to the top housing cover **100**.

[0083] FIGs. 19A-19C show schematic diagrams of the latch **840** in the “reset”, “tripped due to a ground fault” and “key electronic component malfunction” state, respectively. In FIG. 19A, in the “reset” state, the middle portion **843** of the latch is locked into latch groove **805**, of reset shaft **804**. In order to ensure that all the key electronic components of the GFCI are operational, a small simulated ground fault is set up and maintained on the transformer coils **408**. The resulting transformer coil **408** output signal causes the IC to output a drive signal to the coil switching device (not shown) to produce a small steady first current to the solenoid coil **703**, which subsequently produces a small steady first “testing” force. The small steady first “testing” force can be used to either push or pull the latch **840** by means of the solenoid armature **712** so that the latch middle portion **843** tends to engage the latch groove **805** of the reset shaft **804**. The

pushing or pulling first “testing” force is equivalent to the opposite pulling or pushing force, respectively, of the hairspring 844. Thus, in the “reset” position, the first “testing” force generated in the axial direction of the solenoid armature 712 is counterbalanced by the force generated by the hairspring 844 on the latch 840, and latch middle portion 843 is biased to align with latch groove 805.

[0084] As shown in FIG. 19B in “tripped due to a ground fault” state, if a ground fault is detected, the transformer coil 408 outputs a second signal that causes the IC to output a second drive signal to the coil switching device (not shown) to produce a second current to the solenoid coil 703. The second current causes a second force larger than that produced by the hairspring in the axial direction of solenoid armature 712, to drive the solenoid armature 712 towards the latch 840. This action releases the reset shaft 804 from the latch middle portion 843 of latch 840 and places it within cutout 845. Thus the latch block 820 can move downwards and the reset shaft 804 can move upwards under the bias of reset spring 811 and latch block actuation spring 812 to effect the separation of contacts 501, 521 and 601, 621, as previously discussed.

[0085] As shown in FIG. 19C, in the “key electronic component malfunction” state, if one of the key electronic components such as the transformer, the solenoid or the IC of the GFCI malfunctioned, solenoid coil 703 would not apply force to armature 712 as is required to enable resetting of the GFCI device 1. Thus, the coil switching device (not shown) for the transformer fails to produce the required first current to the solenoid coil 703. In absence of the first “testing” force generated by the solenoid coil 703 on the solenoid armature 712, the force generated by the hairspring 844 in the axial direction of the solenoid armature 712 allows latch middle portion 843 to lose its bias to align with groove 805. Thus, the latch block 820 remains in a downward position and reset shaft 804 remains upward under the bias of reset spring 811 and latch block actuation spring 812. Thus, the separation of contacts 501, 521 and 601, 621 is maintained when the components of the GFCI are inoperable or malfunctioning.

[0086] In operation, the latch block assembly 810 can be moved from its “reset” position to its “tripped due to a ground fault” or “key electronic component malfunction” position by the force of reset spring 811 and latch block actuation spring 812 when the latch 840 is unlocked from the

reset shaft **804**. In the “tripped due to a ground fault” state, latch **840** can be unlocked from the reset shaft by the solenoid armature which, when actuated, pushes the striking plate **841** of the latch **840** to cause the latch **840** to slide along the base of the latch block **820** against the force of the hairspring **844**. As the latch **840** slides along the base of the latch block **820**, latch middle portion **843** is withdrawn from the latch groove **805** in the reset shaft **804** and reset shaft **804** is placed in cutout **845** of latch **840**. Thus, the compressive force of the reset spring **811** causes the reset shaft **804** and reset button **802** to move upwards and into contact with the top housing cover **100**, while the compressive force of the latch block actuation spring **812** simultaneously causes the latch block assembly **810** to slide linearly down the reset shaft **804**. In addition, the linear downward movement of the latch block assembly **810** causes the arms **821** of the latch block **820** to contact the cantilevered arm portions of the hot and neutral contact arms **520** and **620**, respectively. The contacts **501**, **521** and **601**, **621** can thus be separated from each other by the force of contact between the latch block arms **821** and the contact arms **520** and **620** as the latch block assembly **810** moves downwardly relative to the reset shaft **804**.

[0087] After the contacts **501**, **521** and **601**, **621** have been separated, latch block assembly **810** continues its downward linear motion until it contacts the circuit desensitizing switch **850** and forces it into electrical contact with the desensitizing contact **851** located in the bottom housing **200**. Thus, only after contacts **501**, **521** and **601**, **621** have been opened is it physically possible to close the desensitizing switch **850** with the desensitizing contact **851**. The desensitizing switch **850** turns off the ground fault detection mechanism when it is closed with the desensitizing contact **851** to prevent the solenoid from continued repeated activation after the GFCI is tripped. Once the latch block assembly **810** has caused the desensitizing switch **850** to contact the desensitizing contact **851**, the GFCI device is considered to be in the fully “tripped” position. In the fully “tripped” position, the reset button abuts the top housing cover **100** by the compressive force of reset spring **811**, and the latch block assembly **810** is kept at its lowermost position by compressive force of the latch block actuation spring **812**. In addition, the position of the latch block assembly **810** keeps contacts **801**, **521** and **601**, **621** completely separated from each other and keeps desensitizing switch **850** in contact with the desensitizing contact **851** when

in the fully “tripped” position. Thus, the current pathways are opened when the GFCI device is in the fully “tripped” position and the ground fault detection mechanism is desensitized.

[0088] The fail safe mode feature keeps the GFCI device in the fully “tripped” position when a component of the GFCI is malfunctioning by including structure that does not permit latch 840 to lock onto the reset shaft 804 and reset the latch block 820 to its reset position. For example, as shown in FIGs. 18A-C, latch 840 can be provided with a middle position 843 between cutouts 845 and 846. Only when the force of hairspring 844 is counterbalanced by the first “testing” force generated by solenoid 703 can the reset shaft 804 lock onto middle portion 843 to lift the latch block 820 to the reset position. If a key component of the GFCI is inoperable or malfunctioning, the GFCI device will enter into the “key electronic component malfunction” state if an attempt is made to reset the GFCI device. For the “key electronic component malfunction” state, as explained earlier, as the latch 840 slides along the base of the latch block 820, latch middle portion 843 passes by the latch groove 805 in the reset shaft 804 and reset shaft 804 moves into cutout 846 of latch 840. Thus, the GFCI device cannot be reset to allow electricity to pass through when a key component is malfunctioning.

[0089] The desensitizing circuit can be any well known circuit for desensitizing an error detection mechanism. The error detection mechanism in the preferred embodiment of the invention can be a ground fault detection mechanism that includes a plurality of transformer coils 408 that detect a change in current flowing through the center of the coils via hot and neutral contact stems 522 and 622. In particular, a ground fault can be sensed by the disclosed configuration because when a ground fault occurs, the current flowing through the hot contact stem 522 will be greater than the current flowing back through the neutral contact stem because a portion of current goes to ground before returning through the neutral contact stem. This net change in current causes a current to be produced in the transformer coils 408 that surround the contact stems 522 and 622. When this produced current reaches a predetermined level, the second electrical current is provided to a solenoid winding 703 which causes the solenoid armature 712 to extend and further push the latch striking plate 841, thus causing the latch block assembly (and eventually the entire GFCI device) to move from the “reset” position to the

“tripped” position, to open the current pathways of the GFCI device and prevent further current from going to ground. As explained earlier, the second current produced in the transformer coils 408 as a result of a ground fault is greater than the first current produced in the transformer coils 408 to maintain a simulated ground fault so that the middle portion 843 of latch 840 is biased to align within latch groove 805 of reset shaft 804 when an attempt is made to reset the GFCI device.

[0090] Fig. 20 shows a flow chart describing another embodiment of the invention. This embodiment of the invention includes a GFCI circuit and mechanism that is arranged to require full functionality of the circuit and mechanism in order to be reset after being tripped. This requirement of full functionality in order to be resettable will insure that a unit that has failed in the tripped state will not be able to be reset.

[0091] GFCI's have been in existence for decades, and have had circuit interrupting mechanisms that could be mechanically reset, restoring power to a load, even though the protective circuitry has failed. This means that such a failed GFCI could provide power to a load without providing protection of personnel.

[0092] This embodiment of the invention includes the utilization of a common, bistable latching relay 883 as the circuit interrupting means. Such a relay requires a momentary energization of its coil to cause it to change state. In other words, if the relay contacts were in the closed state, then an energization of its coil would cause its contacts to go into an open state, and if it was in an open state, an energization of its coil would cause its contacts to go into a closed state. By using this type of relay as the circuit interrupting means in a GFCI, and by using a test ground fault within the GFCI to cause this relay to change states, (in other words, to reset it if it was tripped), the entire circuitry is tested each time the GFCI is test tripped and each time it is reset. If the circuit is not functional when an attempt is made to reset it after a trip and failure, then it will not be possible to reset the unit.

[0093] Fig. 20 shows the logical sequence of operation for resetting the GFCI device. At step S100, a determination of whether the GFCI has been tripped is made. If no, then the GFCI takes no further action and the GFCI operates normally to permit continued current flow through the

device. If the GFCI has tripped, then a determination of whether the reset switch **882** has been activated is made at step **S102**. If no, the GFCI remains tripped and no current passes through the GFCI device. If the reset switch **882** has been activated, then at step **S104** a test current differential is applied to the GFCI mechanism to simulate a ground fault and determine whether the GFCI device is functional. At step **S106** a determination is made as to whether the GFCI is operational as a result of the application of the applied test current differential. If the GFCI is not operational, it is not permitted to be reset and remains tripped with no current passing therethrough. If the GFCI is operational, the test current differential causes an electrical signal to be sent to a bistable latching relay **883** at step **S108**. The bistable latching relay **883** resets the GFCI and closes the main circuit so that current can flow through the GFCI device.

[0094] As shown in Fig. 21 and indicated above in the Summary of the Invention section, the GFCI device can include a switch or a relay, such as a bistable latching relay **883**, connected to a detection mechanism **881**, for example, a current sensing device. The current sensing device is capable of determining whether the outflow of current is different from inflow, and upon sensing a difference between outflow current and inflow current (sensing a possible ground fault), outputting an electrical signal to the relay which then opens and prevents current from flowing through the GFCI. The device includes a reset switch **882** that sets up a test condition for the GFCI device. If the reset switch **882** is activated and test conditions indicate that the GFCI is functioning properly, an electrical signal is provided to the relay which then closes and permits current to pass through the GFCI.

[0095] Although the preferred embodiments of the invention are disclosed with regard to a ground fault interruption detection circuit, it is possible to incorporate the invention into different types of circuits in which a current pathway is required to be quickly and efficiently opened and prevented from being reclosed in the event of a key component failure. For example, the principles of the invention can be applied to a device that includes an arc fault detection circuit, appliance leakage fault detection circuit, immersion fault detection circuit, test detection circuit or other types of circuit interrupters.

[0096] In addition, several practical configurations of the circuit fall within the scope of the invention. For example, in order to ensure that the relay does not repeatedly change states when the GFCI detects a ground fault or other error (or is attempted to be reset), a separate set (or sets) of contacts can be placed within the circuit to prevent the relay from repeatedly changing states. The separate contacts can later be automatically or manually actuated to allow the relay to operate again.

[0097] The material from which the GFCI device is made can also vary without leaving the scope of the invention. In particular, the current pathway structure can be made from any well known electrically conductive material, but is preferably metal and, more specifically, is preferably copper. The transformer coils are preferably made from copper and can be separated from each other and from the exterior of the transformer boat by disc shaped washers. The washers are preferably plastic, but can be made of any electrical insulating material. In addition, instead of using washers, it is possible that the transformer coils can be separated by other electrically insulative devices, such as integral extensions of the transformer boat and/or insulative wrapping material over the transformer coils. The latch block is preferably made from a plastic material, but can be made from any electrically insulative material. The housing structures are also preferably made from a plastic material, but can be made from any electrically insulative material. For, example, the top housing cover 100 can be made from wood, ceramic, marble or other eclectically insulative material that might match the decor of a person's house. Both the transformer boat and solenoid bobbin are preferably made from a plastic material, but can be made from any material that is electrically insulative.

[0098] The current pathway structure is preferably constructed as simply as possible to keep the heat generated by the resistance of the current pathway at a minimum. Accordingly, although the contacts 521, 621 and 501, 601 are disclosed as structures that are press fit into throughways located at ends of the two contact arms and two output terminals, respectively, it is not beyond the scope of the invention to make the contacts integral with their respective contact arm or output terminal. In addition, the contacts could be welded, soldered or otherwise electrically connected to their respective contact arms or output terminals.

[0099] As stated previously, the single electrical connection in each of the current pathways is preferably a solder type connection, but can be any other well known type of electrical connection such as a weld or clamping arrangement.

[00100] The springs for use in the test/reset switch are preferably coil type springs and the hairspring **844** is a wire type spring. However, a leaf spring, spring arm, coil spring or any other well known type of spring can be used for the reset spring **811**, latch block actuation spring **812** or even the hairspring **844**.

[00101] For example, a coil spring as disclosed in Application No. 09/251,427 (referred to above) could be used instead of the hairspring **844** to counterbalance the input from the solenoid **703**. Specifically, a coil spring could be placed between the latch block **820** and the striking plate **841** of the latch **840** to counterbalance the force input from the solenoid **703**.

[00102] It will be apparent to those skilled in the art that various modifications and variations can be made in the error detection device of the invention without departing from the spirit and scope of the invention. Thus, it is intended that the invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.